Name, Date and Time Specification

You can use a name, a date, a time or a range of names, dates and times to select Natural library objects, system messages, command processor sources, FDTs and Natural-related objects.

Below is information on the specification options provided for:

- Name
- Date
- Time

Name

You can specify a name or a range of names.

In the list of options below, *value* is any combination of one or more characters:

	Input	Selected Items
	value	A single item.
	*	All items.
	>	
	?	All items with any single character for each question mark (?) entered.
Leading Characters	value*	All items whose names begin with <i>value</i> .
		Example: AB*
		Selected: AB, AB1, ABC, ABEZ
		Not selected: AA1, ACB
Wildcard	value?	All items whose names begin with <i>value</i> and end with any single character for each question mark (?) entered.
		Example: ABC?
		Selected: ABCA, ABCZ
		Not selected: AXC, ABCAA
	value?value?	Asterisks (*) and question marks (?) can be combined in any order.
	value*value?	Example: A?C*Z
		Selected: ABCZ, AXCBBBZ, ANCZ
	value?value	Not selected: ABDEZ, AXCBBBZA
Start Value	value>	All items whose names are greater than or equal to value.
		Example: AB>
		Selected: AB, AB1, BBB, ZZZZZZZ
		Not selected: AA1, AAB
End Value	value<	All items whose names are less than or equal to value.
		Example: AX<
		Selected: AB, AWW, AX
		Not selected: AXA, AY

Copyright Software AG 2001

Note:

The parameter specification option New Value only allows leading characters (asterisk (*) notation). See Rules for New Values in Set Global Parameters (Settings).

Date

All date values within the Object Handler are specified in international date format.

You can specify a date, a range of dates, a special date or a range of special dates. A date must be specified in the format YYYY-MM-DD (YYYY = year, MM = month, DD = day).

In the list of options below, value is any combination of one or more numbers:

	Input Value	Specification
Date	YYYY-MM-DD	Precise date.
		Example: 2001-02-15
Leading characters	value*	All items whose dates begin with value.
		Example: 2001* Selected: 2001-01-01, 2001-12-31 Not selected: 2000-12-31, 2002-01-01
Start value	value>	All items whose dates are greater than value.
		Example: 2001-05> Selected: 2001-05-01, 2001-12-31, 2002-01-01, 2002-12-31 Not selected: 2001-04-31, 2000-12-31
		Special dates can be used as <i>value</i> .
End value	value<	All items whose dates are less than <i>value</i> . Example: 2001-02< Selected: 2000-05-01, 2000-12-31, 2001-01-01, 2001-01-31 Not selected: 2001-02-01, 2001-05-18
		Special dates can be used as value.
Special Dates	•	
TODAY (+/-nnnn)		The date of the current day. The day can be followed by +nnnn or -nnnn where nnnn is the maximum of 4 numeric digits. The resulting date is computed as the date of the current day plus or minus nnnn days. Example: current date is 2001-03-01 TODAY +5 results in 2001-03-06
<u>YES</u> TERDAY		The date of the day before the current day.
<u>MON</u> TH		The date range of the current month. FMDATE: Starts with the first day of the current month. TODATE: Ends with the last day of the current month. If the values of FMDATE and TODATE are identical, the selection is restricted to one day.
<u>YEA</u> R		The date range of the current year. FMDATE: Starts with the first day of the current year. TODATE: Ends with the last day of the current year. If the values of FMDATE and TODATE are identical, the selection is restricted to one year.

Note:

The parameter specification option New Value only allows leading characters (asterisk (*) notation). See Rules for New Values in Set Global Parameters (Settings).

Copyright Software AG 2001 3

Time

You can specify a time or a range of time. The time must be specified in the format HH:II:SS (HH = hours, II = minutes, SS = seconds).

In the list of options below, *value* is any combination of one or more numbers:

	Input Value	Selection
Time	HH:II:SS	Precise Time.
		Example: 14:15:16
Leading characters	value*	All items for the time frame indicated by the <i>value</i> before the asterisk are selected.
		Example: 13:* Selected: 13:00:00, 13:10:53, 13:59:59 Not selected: 12:59:59, 14:00:00